Alternating Gradient Synchrotron Department
Relativistic Heavy Ion Collider Project
BROOKHAVEN NATIONAL LABORATORY
Upton, New York 11973

Spin Note

AGS/RHIC/SN No. 013
(January 19, 1996)

Spin Rotation Matrices for Spin Tracking

A. Luccio

October 30, 1995

For Internal Distribution Only

BNL-62371
UC-414
AGS/AD/96-1
INFORMAL

SPIN ROTATION MATRICES FOR SPIN TRACKING

A. Luccio

October 30, 1995

ALTERNATING GRADIENT SYNCHROTRON DEPARTMENT

BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.
UPTON, LONG ISLAND, NEW YORK

UNDER CONTRACT NO. DE-AC02-76CH00016 WITH THE
UNITED STATES DEPARTMENT OF ENERGY

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

Spin Rotation Matrices for Spin Tracking

A.Luccio

For spin trackingin a synchrotron[1] it is convenient to express the spin rotation in each machine element in matrix form

(1) $$\mathbf{S} = \hat{\mathbf{M}}\mathbf{S}_0$$

Start from the BMT equation [2]

(2) $$\frac{d\mathbf{S}}{dt} = \frac{e}{\gamma m}\mathbf{S}\times\mathbf{F}$$

with

(3) $$\mathbf{F} = (1+G\gamma)\mathbf{B}_\perp + (1+G)\mathbf{B}_\parallel + \left(G\gamma + \frac{\gamma}{1+\gamma}\right)\frac{\mathbf{E}\times\boldsymbol{\beta}}{c}$$

containing the magnetic field components transverse and longitudinal with respect to the velocity **v**.

Assume E = 0, and use vector identities to express the magnetic field *components* in terms of the magnetic field **B**

(4) $$(\mathbf{v}\times\mathbf{B}_\perp)\times\mathbf{v} = (\mathbf{v}\cdot\mathbf{v})\mathbf{B}_\perp - (\mathbf{v}\cdot\mathbf{B}_\perp)\mathbf{v} = v^2\mathbf{B}_\perp$$

Since $$\mathbf{v}\times\mathbf{B}_\perp \equiv \mathbf{v}\times\mathbf{B}$$

obtain

(5) $$\mathbf{B}_\perp = \frac{1}{v^2}(\mathbf{v}\times\mathbf{B})\times\mathbf{v}$$

Also

(6) $$\mathbf{v}\cdot\mathbf{B} = vB_\parallel, \quad \mathbf{B}_\parallel = \frac{\mathbf{v}}{v}B_\parallel$$

then

(7) $$\mathbf{B}_\parallel = \frac{1}{v^2}(\mathbf{v}\cdot\mathbf{B})\mathbf{v}$$

After some readjustment

(8) $$\mathbf{F} = (1+G\gamma)\mathbf{B} - G(\gamma-1)\frac{1}{v^2}(\mathbf{v}\cdot\mathbf{B})\mathbf{v}$$

Use a coordinate system that revolves around the accelerator[3,4]. The axis z , longitudinal, is tangent to the "equilibrium" orbit, x and y are the displacements with respect to this orbit, radial and vertical, respectively. Call s the longitudinal coordinate along the eq-orbit. In this coordinates, the derivative of a vector **a** is

(9) $$\frac{d\mathbf{a}}{ds} = \frac{da_x}{ds}\hat{\mathbf{x}} + a_x\frac{d\hat{\mathbf{x}}}{ds} + \frac{da_y}{ds}\hat{\mathbf{y}} + \frac{da_z}{ds}\hat{\mathbf{z}} + a_z\frac{d\hat{\mathbf{z}}}{ds}$$

with

(10) $$\frac{d\hat{\mathbf{x}}}{ds} = \frac{\hat{\mathbf{z}}}{\rho}, \quad \frac{d\hat{\mathbf{z}}}{ds} = -\frac{\hat{\mathbf{x}}}{\rho}$$

with ρ the local curvature radius of the eq-orbit.

Because of Eqs. (9) and (10) the velocity is

(11) $$\mathbf{v} = \frac{d\mathbf{r}}{dt} = \left[x'\,\hat{\mathbf{x}} + y'\,\hat{\mathbf{y}} + (1+\frac{x}{\rho})\hat{\mathbf{z}}\right]\frac{ds}{dt}$$

Primes denote differentiation with respect to s.

Make the assumption that in a machine element the magnetic field and the orbit don't change. If this is not the case, we will slice each element and write matrices for each slice.

Use Eqs. (9), (10), (11), and

$$\frac{e}{\gamma m} = \frac{v}{(B\rho)}$$

to rewrite Eq. (2) as follows

(12) $$\frac{d\mathbf{S}}{ds} = \mathbf{S}\times\mathbf{f}$$

with

(13) $$\mathbf{f} = \frac{h}{(B\rho)}\left[(1+G\gamma)\mathbf{B} - G(\gamma-1)(\mathbf{r}'\cdot\mathbf{B})\mathbf{r}'\right]$$

where

$$h = h(x, x', y') = \sqrt{x'^2 + y'^2 + (1 + x/\rho)^2}$$

and

$$\mathbf{r}' = \frac{\mathbf{v}}{v}$$

is the trajectory angle.

Using Eqs. (9) and (10), Eq. (12) is equivalent to three scalar diff. equations

$$\text{(14)} \qquad \begin{cases} S_x' = f_z S_y - (f_y - \frac{1}{\rho}) S_z \\ S_y' = f_x S_z - f_z S_x \\ S_x' = (f_y - \frac{1}{\rho}) S_x - f_x S_y \end{cases}$$

The system (14) yields three third order formally identical linear equations for the three components of the spin

$$\text{(15)} \qquad S''' + \omega^2 S' = 0$$

with

$$\text{(16)} \qquad \omega^2 = f_x^2 + (f_y - \frac{1}{\rho})^2 + f_z^2$$

The general integral of Eq. (15) is

$$S = C_1 + C_2 \cos \omega \delta s + C_3 \sin \omega \delta s$$

with δs the orbit path length through the machine element along the eq-orbit. The constants of integration can be found as a function of the initial values of the spin components using S, S', S'' and the original system. We obtain a matrix **M** [Eq. (1)] for the result

$$\text{(17)} \qquad \begin{pmatrix} 1-(B^2+C^2)c & ABc + Cs & ACc - Bs \\ ABc - Cs & 1-(A^2+C^2)c & BCc + As \\ ACc + Bs & BCc - As & 1-(A^2+B^2)c \end{pmatrix}$$

with

$$\begin{cases} c = 1 - \cos \omega \delta s \\ s = \sin \omega \delta s \end{cases}, \quad A = \frac{f_x}{\omega}, \quad B = \frac{f_y - 1/\rho}{\omega}, \quad C = \frac{f_z}{\omega}$$

Particular cases (to first order in x and y)

1- Horizontal bend (field vertical). Rectangular Magnet.

$$B_x = 0, \quad B_y = B\rho/\rho, \quad B_z = 0$$

$$f_x = 0, \quad f_y - \frac{1}{\rho} = \frac{G\gamma}{\rho} - \frac{1+G\gamma}{\rho}\frac{x}{\rho}, \quad f_z = 0$$

$$A = 0, \quad B = 1, \quad C = 0$$

The matrix

$$\begin{pmatrix} \cos\delta\psi & 0 & \sin\delta\psi \\ 0 & 1 & 0 \\ -\sin\delta\psi & 0 & \cos\delta\psi \end{pmatrix} \tag{18}$$

represents a rotation of the spin around the vertical axis. The angle of rotation is

$$\delta\psi = \omega\,\delta s = \left[G\gamma - (1+G\gamma)\frac{x}{\rho}\right]\delta\theta$$

with $\delta\theta = \delta s/\rho$ the bend angle.

2- Quadrupole.

$$k_1 = -\frac{\partial B/\partial r}{(B\rho)}$$

$$B_x = k_1(B\rho)y, \quad B_y = k_1(B\rho)x, \quad B_z = 0$$

$$\frac{1}{\rho} = 0$$

Then

$$f_x = k_1(1+G\gamma)y, \quad f_y - 1/\rho = k_1(1+G\gamma)x, \quad f_z = 0$$

$$\omega = k_1(1+G\gamma)r, \quad r = \sqrt{x^2+y^2}$$

$$A = y/r, \quad B = x/r, \quad C = 0$$

The matrix is

$$\frac{1}{r^2}\begin{pmatrix} y^2 + x^2\cos\delta\psi & xy(1-\cos\delta\psi) & -xr\sin\delta\psi \\ xy(1-\cos\delta\psi) & x^2 + y^2\cos\delta\psi & yr\sin\delta\psi \\ xr\sin\delta\psi & -yr\sin\delta\psi & \cos\delta\psi \end{pmatrix} \tag{19}$$

with

$$\delta\psi = \omega\,\delta s$$

If $x = 0$ (no horizontal motion) Eq. (18) represents a rotation around the radial x. axis by an angle proportional to 1+Gγ. If $y = 0$, a rotation around the vertical y axis by an angle proportional to Gγ.

3- Thin Siberian Snake.

In this device the field is in an horizontal plane at an angle ϕ with the z axis.

$$B_x = B_{SN}\sin\phi, \quad B_y = 0, \quad B_z = B_{SN}\cos\phi$$

It is

$$f_x = \frac{1}{(B\rho)}(1+G\gamma)B_{SN}\sin\phi, \quad f_y = 0, \quad f_z = \frac{1}{(B\rho)}(1+G\gamma)B_{SN}\cos\phi$$
$$\omega = (1+G\gamma)B_{SN}$$
$$A = \sin\phi, \quad B = 0, \quad C = \cos\phi$$

producing the matrix

$$\begin{pmatrix} 1-\cos^2\phi(1-\cos\delta\psi) & \cos\phi\sin\delta\psi & \sin\phi\cos\phi(1-\cos\delta\psi) \\ -\cos\phi\sin\delta\psi & \cos\delta\psi & \sin\phi\sin\delta\psi \\ \sin\phi\cos\phi(1-\cos\delta\psi) & -\sin\phi\sin\delta\psi & 1-\sin^2\phi(1-\cos\delta\psi) \end{pmatrix} \tag{20}$$

with the spin rotation angle

$$\delta\psi = \omega\,\delta s = (1+G\gamma)\frac{B_{SN}\delta s}{(B\rho)}$$

Acknowledgments

Discussions with Tom Roser and Mike Syphers are gratefully acknowledged.

References

[1] A.Luccio. Numerical Spin Tracking in a Synchrotron. Brookhaven Report BNL-52481, September 14, 1995.

[2] B.W. Montague. Polarized Beams in High Energy Storage Rings. Phys. Reports 113, No. 1 (1984) 1-96.

[3] S.Y. Lee. On the Polarized Beam Acceleration in Medium Energy Synchrotrons. Lecture note presented at RCNP-Kikuchi School on "Physics at Intermediate Energy", Osaka, Nov. 15-19, 1992.

[4] E.D. Courant and R.D. Ruth. The Acceleration of Polarized Protons in Circular Accelerators. Brookhaven Report BNL 51270/UC-28, September 12, 1980.